3S LIFT

SAFE | SIMPLE | SPECIALIZED
ACCESS EQUIPMENT

Sealed Self-Retracting Lifeline

Fall Protection for Safety and Free Movement

Ficont Industry (Beijing) Co., Ltd.
No. 15, Chuangyi East 2nd Road,
Xiji Development Zone,
Tongzhou, Beijing, China
+86 10 69597866
info-china@3SLift.com

Ficont Industry (Beijing) Co., Ltd.
1005, SK Tower, No. 6 Jia,
JianGuoMenWai Avenue,
Beijing, 100022, China
+86 10 61518677
info-china@3SLift.com

Ficont Industry (Tianjin) Co., Ltd.
No. 8, Cuiyuan Road, Wuqing
Development Zone,
Tianjin, China
+86 22 22140477
info-china@3SLift.com

3S Americas, Inc.
2840 Guilder Drive, Suite 100
Plano, TX 75074, USA
+1 312 623 2662
info@3SAmericas.com

3S Europe GmbH
Erdmannstr. 10
22765 Hamburg, Germany
+49 40 325 188 87
info@3SEurope.de

3S Lift India Private Limited
No. 2C Shyams Garden, Khadar
Nawaz Khan Road, Nungambakkam,
Chennai - 600006, India
+91 4466255559
info-india@3SLift.com

3S LIFT

SAFE | SIMPLE | SPECIALIZED
ACCESS EQUIPMENT

Sealed Self-Retracting Lifeline

Fall Protection for Safety and Free Movement

Working at height can make it challenging for employees to fully concentrate on the task at hand while staying safe at the same time. They can be so engaged with completing a job that they may miss important safety steps. Alternatively, safety equipment can sometimes constrict the technicians' movements and hinder them from efficiently completing their tasks.

3S Lift helps technicians be more productive and feel safe with our Sealed Self-Retracting Lifeline Fall Protection System. This lightweight, durable fall protection has a self-retracting, built-in wire rope that provides guaranteed safety for personnel while allowing them to move freely in the work area. Should a fall occur, the brake will self-engage to arrest the fall. The 3S Lift Sealed Self-Retracting Lifeline allows technicians to perform repairs and installations at height with complete peace of mind.

Sealed Self-Retracting Lifeline Specifications

Model	SRL-15S / SRL-25S
Rated load	30–140 kg (60-310 lbs)
Maximum force	6 kN at 100 kg load, 8 kN at 140 kg load
Wire rope length	15 m / 25 m
Wire rope diameter	5 mm
Maximum braking distance	1 m
Weight (incl. wire rope)	13.5 kg / 30 kg
Constructing materials	Aluminum alloy housing, stainless steel components
Anti-corrosion class	C5-M
Protection class	IP69K
Certification	CE
Compliant with standard	EN360, GB 24544-2009, ANSI Z359.14-2014, CSA Z259.2.2-17

Carrying Handle
The carrying handle allows for convenient transportation.

Ergonomic Wire Rope Handle
The ergonomic wire rope handle provides added comfort when making connections. It also seals the wire rope after it is withdrawn, protecting it from exposure to the elements.

Swivel Hook
The swivel hook limits twisting of the lifeline.

Impact Indicator
The impact indicator provides visual indication of fall arrest to allow for repair or replacement.

Lock Hook
The lock hook reduces the chance of accidental disengagement.

On-Shore And Offshore Use
Designed for both, on-shore and offshore, the SRL-15S and the SRL-25S can operate in the harshest environments.

Self-Retracting
The self-retracting design allows he lifeline to be extended and retracted, always keeping it taut. This provides freedom of movement without compromising safety.

Self-Locking
The self-locking fall arrest mechanism engages instantly, should a fall occur.

Durable Design
The product's durable design features anti-corrosive protection to avoid damage from the environment.

Simple Installation And Disassembly
The reliable, self-locking lifeline is easy to install, use and disassemble.

No Maintenance From User
The lifeline is thoughtfully designed to require no maintenance from the user.

Extended Serviceable Life With Minimal Maintenance Costs
The 3S Lift Sealed Self-Retracting Lifeline offers an extended serviceable life with minimal maintenance costs.

Sealed Design
The sealed design protects the lifeline from the elements and prevents damage from grease, moisture, and dirt.